

**PRODUCT DATA SHEET Nano Real Stone**  
*Slim stone veneer*



**Surfaces:** Flexible stone veneer comes from split slate rock. This is cut to a thickness of 0.6 mm and placed on one side of the mounting material (MDF or chipboard plates). Offset paper ensures plate stability. In the case of front surfaces in frequent contact with dirt and moisture (e.g. kitchens or bathrooms), the surface may be sealed upon request.

## TECHNICAL DETAILS

<b>Support:</b>	MDF or chipboard (16, 18 or 19 mm thick)
<b>Front:</b>	0.6 mm thin natural stone veneer, sealed.
<b>Back:</b>	White offset paper, or with colour similar to the front
<b>Dimensions:</b>	Large format plates, 2400 x 1200 mm (for production orders) or 1200 x 610 mm (at stock)
<b>Features:</b>	<ul style="list-style-type: none"> <li>▪ Authentic natural stone on the surface</li> <li>▪ Surface sealing optimally protects this product against dirt or water splashes. Very effective cleaning and care can be performed without any problems using common household cleaning agents.</li> <li>▪ Stone veneer can be easily cut or drilled using common carpentry tools.</li> <li>▪ The veneer may be bonded to the mounting plate using different types of adhesive (epoxide adhesives, polyurethane adhesives, polymer adhesives, glue)</li> </ul>
<b>Applications:</b>	<ul style="list-style-type: none"> <li>▪ Kitchen area</li> <li>▪ Bathroom and sanitary areas</li> <li>▪ Furniture and door designs</li> <li>▪ Walls and interior design</li> </ul>

Otto-Vertrieb GmbH & Co. KG  
 09/09/2016

**Disclaimer:** the information contained in this data sheet is intended as a suggestion for optimum use of product. No responsibility is assumed for production results.