

TECHNICAL DATASHEET

DuroTec Nano Supermatt

TECHNICAL DATA

- Composite panel 19mm thick with Supermatt scratch-resistant surface supermatt-finished and antifingerprint surface coating.
- Raw material MDF 19mm, backside coating with white melamine resin or, on request, of the same colour as the front side.
- Panel size 2800 x 1220 x 19mm.
- Colours: black SM, white SM, cream SM, anthracite grey SM.
- Supermatt lacquered scratch-resistant finish with antifingerprint-effect.
- Gloss level: 3 Gloss.
- Resistance to chemical agents according to EN 438-2:2005/Group 1,2,3 Level 5.
- Scratch resistance according to EN 438-2:1991 Level 2 > 3 Newton.
- Abrasion resistance according to EN 438-2:2005 AT= 250 turns.
- Water vapour resistance pursuant to EN 438-2:2005, Level 5 >> no change, water-resistant.
- Smooth matt surface, silky to the touch: no reflection, dirt-resistant.
- Eco-friendly panel: solvent and formaldehyde-free.
- Colour-stable with UV resistance.
- Micro-scratches can be removed by passing a hot iron over them. Maximum temperature of 120°C for a 10-second application.
- Slight micro-scratches can be removed using a common household cleaning sponge.